



IMPAK AL 2418

The **IMPAK AL 2418 Fully Automatic L Sealer** is equipped with 2 non-stick Teflon coated sealing knives which ensures a neat and strong seal. State of the art HMI ensures excellent operator interface with all machine parameters. Safety transparent hood increases the safety for the operator. The machine also features a choice of vertical or horizontal type photocell sensor to suit various product sizes and thickness. The machine can automatically adjust the feeding length and reel of the waste film. Multi row micro perforator wheels ensure flexibility when tailoring package shrinking properties. Back-up brush roller increases perforator life. It is equipped with a buzzer for fault alerts.

SPECIFICATIONS

- Machine Dimension: 75" Long x 33" Wide x 60" High
- Sealing Dimension: 24" Long x 18" Wide
- Packing Speed: 30 packs/minute
- Power: 220 Volts, 1 Phase, 8 Amps, 60 Hz
- Weight: 795 Lbs

FEATURES

- Teflon Coated Sealing Knives
- HMI Operator Interface
- Adjustable Conveyor Time
- Adjustable Conveyor Speed
- Adjustable Sealing Time
- Vertical/ Horizontal Photocell Sensors
- Manual/Automatic Product In-Feed
- Film Micro Perforator System
- Back-Up Perforator Brush Roller
- Easily Adjustable Infeed Table and Inverting Head Height
- Heavy Duty Casters
- Rugged Steel Construction
- Low Maintenance
- Easily Accessible Electrical Panel
- Durable Paint Finish
- Transparent Safety Hood
- Recessed Scrap Rewinder