

IMPAK SMC 1519 COMBINATION SYSTEM



IMPAK SMC 1519 Combination System

The **IMPAK 1519 Combination System** is equipped with a non-stick Teflon coated sealing blade which ensures a neat and firm seal. It has an overheat protect function that extends the lifespan of the machine. It includes a hand clamping device designed to assist in avoiding damage to the product while increasing the safety for the operator. It features dual magnetic clamps which increase the sealing pressure ensuring a firm, strong and consistent seal. The Shrink tunnel has an advanced heater bank and an adjustable high speed blower to re-circulate air, reducing the heat-up time and heat loss. This ensures the best packing results. It is equipped with heavy duty casters with locks for better portability.

SPECIFICATIONS

- Machine Dimensions: 77" Long × 27" Wide × 53" High
- Max. Packing Size: 15" Long × 12" Wide × 6" High
- Packing Speed: 10-12/minute (Product + Operator Dependent)
- Tunnel Opening: 16" Wide x 7" High
- Power: 220 Volts, 1 Phase, 23 Amps, 60 Hz, 4.5 KW
- Weight: 662 Lbs

FEATURES

- Teflon Coated Sealing Blade
- Dual-Magnet Clamping
- Adjustable Conveyor Time
- Adjustable Sealing Time
- Overheat Protect Function
- Quick Film Loading Cradle Design
- Film Micro Perforator System
- Adjustable Stainless Steel Loading Table
- Hand Clamping Safety Device
- Adjustable Height Discharge Conveyor Belt
- Transition Rollers Between Sealer & Tunnel
- Heavy Duty Casters
- Rugged Steel Construction
- Low Maintenance
- Easily Accessible Electrical Panel
- Durable Paint Finish