

## IMPAK SMC 1622 L SEALER



IMPAK SMC 1622



IMPAK SMC 1622 WITH OPTIONAL STR 1808 SHRINK TUNNEL

The **IMPAK SMC 1622 L Sealer** is equipped with an anti-adhesive Teflon coated sealing blade which ensures a neat and strong seal. It has an overheat protect function that extends the lifespan of the sealer. It includes a seal head clamping device designed to assist in avoiding damage to the product while increasing the safety for the operator. It features dual magnetic clamps which increase the sealing pressure ensuring a firm, strong and consistent seal. It is equipped with heavy duty casters with locks for better portability.

### SPECIFICATIONS

- Machine Dimensions: 63" Long x 30" Wide x 39" High
- Max. Sealing Dimension: 16" Wide x 22" Long
- Power: 220 Volts, 1 Phase, 9 Amps, 60 Hz, 1 KW
- Packing Speed: 10-12/minute
- Weight: 300 Lbs

### FEATURES

- Large 16" x 22" Seal Area
- Dual-Magnet Clamping
- Teflon Coated Sealing Blade
- Adjustable Conveyor Time
- Adjustable Conveyor Speed
- Adjustable Sealing Time
- Overheat Protect Function
- Quick Film Loading Cradle Design
- Film Micro Perforator System
- Adjustable Stainless Steel Loading Table
- Hand Clamping Safety Device
- Adjustable Height Discharge Conveyor Belt
- Heavy Duty Casters
- Rugged Steel Construction
- Low Maintenance
- Easily Accessible Electrical Panel
- Durable Paint Finish