

HEAVY DUTY SHRINK TUNNEL

MODEL: HDT2822



FEATURES

TUNNEL CHAMBER

- Digital Tunnel Temperature Control
- Open Coil Heating Element Guaranteed for 10 Years
- High Volume, Single Chamber Design with Variable Air Velocity Control
- One Horsepower Motor with Special High Efficiency Blower Wheel
- Automatic Cool Down Extends Heating Element Life
- Built In High Limit Safety Control for Blower Motor
- Pyrogel XT Insulation

CONVEYOR FEATURES

- Quick Change 5/8" Diameter Live/Dead Rollers with 1 1/2" Spacing
- Blower Cooled Rollers
- Unique Pre-Shrink Feature Allows for 25% More Bottom Shrink
- One Quarter Horsepower Motor with Adjustable Conveyor Speeds of Up to 100 Feet per Minute
- Heavy Duty Hollow Pin Chain
- Twin Bearing Idler Sprockets



Model HDT2822

OTHER FEATURES

- Heavy Duty, Heavy Gauge Construction Throughout
- Control Panel Dual Exhaust Fan
- Heavy Gauge Adjustable Height Console With Levelers And 3" Casters
- Stainless Steel Model Available
- Two Year Warranty

MODEL SPECS

INSIDE TUNNEL DIMENSIONS	28" L, 22" W, 8" H (71 L, 56 W, 21 H cm)
CONVEYOR	Variable Speed, Quick Change Live/Dead Silicone Covered Rollers with 1.5" Spacing
CONVEYOR SPEED	1-100 Feet Per Minute (LDR); 0-50 Feet Per Minute (TMB,SWB)
OVERALL DIMENSIONS	54" L, 35" W, 65" H (137 L, 89 W, 165 H cm)
POWER REQUIREMENTS	230 Volts, 45 Amp, Single Phase
WATTAGE	9,000 Watts
WEIGHT	880 lbs. (400 kg)

AVAILABLE OPTIONS

- Stainless Steel Construction (HDT2822S)
- Roller Spacing: 1"
- Stainless Steel Wire Mesh Belt Conveyor
- Non-stick Mesh Belt Conveyor
- Non-stick Mesh Belt Overlay (for Live/Dead Roller)
- Hydraulic Easy Lift Adjustable Height Console
- 12" High Tunnel Opening
- Pack Cooler Fan (For Polyethylene)
- Product Guide Rails
- Left Hand Reverse Flow

Revised 2015

4580 E. 71 Street Cleveland, OH 44125
www.HeatSealCo.com

Phone: (216) 341-2022 Fax: (216) 341-2163
CustServ@HeatSealCo.com

