

HEAVY DUTY SHRINK TUNNEL

MODEL: HDT6022



FEATURES

TUNNEL CHAMBER

- Digital Tunnel Temperature Control
- Open Coil Heating Element Guaranteed for 10 Years
- High Volume, Single Chamber Design with Variable Air Velocity Control
- One Horsepower Motor with Special High Efficiency Blower Wheel
- Automatic Cool Down Extends Heating Element Life
- Built In High Limit Safety Control for Blower Motor
- Pyrogel XT Insulation

CONVEYOR FEATURES

- Quick Change 5/8" Diameter Live/Dead Rollers with 1 1/2" Spacing
- Blower Cooled Rollers
- Unique Pre-Shrink Feature Allows for 25% More Bottom Shrink
- One Quarter Horsepower Motor with Adjustable Conveyor Speeds of Up to 100 Feet per Minute
- Heavy Duty Hollow Pin Chain
- Twin Bearing Idler Sprockets



Model HDT6022

OTHER FEATURES

- Heavy Duty, Heavy Gauge Construction Throughout
- Control Panel Dual Exhaust Fan
- Heavy Gauge Adjustable Height Console With Levelers And 3" Casters
- Stainless Steel Model Available
- Two Year Warranty

MODEL SPECS

| | |
|---------------------------------|---|
| INSIDE TUNNEL DIMENSIONS | 60" L, 22" W, 8" H (152 L, 56 W, 21 H cm) |
| CONVEYOR | Variable Speed, Quick Change Live/Dead Silicone Covered Rollers with 1.5" Spacing |
| CONVEYOR SPEED | 1-100 Feet Per Minute (LDR); 0-50 Feet Per Minute (TMB,SWB) |
| OVERALL DIMENSIONS | 85" L, 35" W, 65" H (216 L, 89 W, 168 H cm) |
| POWER REQUIREMENTS | 230 Volts, 60 Amp, Three Phase Circuit with Ground |
| WATTAGE | 18,000 Watts |
| WEIGHT | 1,520 lbs. (690 kg) |

AVAILABLE OPTIONS

- Stainless Steel Construction (HDT6022S)
- Roller Spacing: 1"
- Stainless Steel Wire Mesh Belt Conveyor
- Non-stick Mesh Belt Conveyor
- Non-stick Mesh Belt Overlay (for Live/Dead Roller)
- Hydraulic Easy Lift Adjustable Height Console
- 12" High Tunnel Opening
- Pack Cooler Fan (For Polyethylene)
- Product Guide Rails
- Left Hand Reverse Flow

Revised 2015

