

COMPACT SHRINK TUNNEL

MODEL: T2015



FEATURES

TUNNEL CHAMBER

- 6" H by 15" W Tunnel Opening
- Analog Tunnel Temperature Control
- High Velocity Turbo Tunnel Design
- Automatic Cool Down Extends Heating Element Life

CONVEYOR FEATURES

- Variable Speed Belt Conveyor With Adjustable Heat For Bottom Shrink Control
- Transition Conveyor

OTHER FEATURES

- Heavy Gauge Steel Construction
- Stainless Steel Model Available
- Two Year Warranty



Model T2015
with optional leg kit and 8" high tunnel opening

MODEL SPECS

INSIDE TUNNEL DIMENSIONS	20" L, 15" W, 6" H (51 cm L, 38 cm W, 15 cm H)
CONVEYOR	Variable Speed, Heated Silicone Belt
CONVEYOR SPEED	0-20 FPM (0-6 meters per minute)
OVERALL DIMENSIONS	40" L, 20" W, 48" H (102 cm L, 51 cm W, 122 cm H)
POWER REQUIREMENTS	115 Volts, 20 Amp, Single Phase
WATTAGE	Tunnel: 2,000 Watts; Belt: 500 Watts
WEIGHT	172 lbs. (78 kg)

AVAILABLE OPTIONS

- Stainless Steel Construction (T2015S)
- Digital Temperature Control
- Painted Console Leg Kit with 3" Casters
- Stainless Console Leg Kit with 3" Casters
- Export Wiring: 220 Volt
- Left Hand Reverse Flow

