

EMPLEX

BAG SEALING SOLUTIONS

MPS 7100 Series Continuous Band Sealer

The MPS 7100 series are stand alone bag sealers capable of sealing bags up to 900 grams / 2 pounds in weight without the use of a conveyor (based on an 8" / 203 mm wide bag, 2 mil / 50 micron thick) . These sealers can seal bags up to 12 mil / 300 micron in thickness at production rates (6 mil / 150 micron maximum when gusseted). These sealers are also ideal for when the speed of an MPS 6000 series machine is not enough to meet your manufacturing needs. Designed for 24/7 operation, these sealers are suitable for all production environments.



Electrical:	120 volts, 9 amps.
Infeed Direction:	Right to Left.
Motor:	Variable Speed DC drive.
Seal Throat Depth:	70 mm / 2.75".
Sealing Section:	254 mm / 10" of heating. 254 mm / 10" of cooling.
Variable Speed:	Up to 20 m / 800" per minute.
Sealing Width:	6 mm / 1/4" standard.
Sealer Operation:	Vertical or Horizontal.
Temperature Range:	0-230 degrees C. 0-445 degrees F.
Temperature Controller:	Digital PID autotune controller.

Model	Configuration
MPS 7100	Standard Sealer
MPS 7110	Standard Sealer with Front End Trimmer
MPS 7120	Standard Sealer with Emboss Coder
MPS 7130	Standard Sealer with Dry Ink Printer
MPS 7150	Standard Sealer with Front End Trimmer & Dry Ink Printer
MPS 7160	Standard Sealer with Front End Trimmer & Emboss Coder

Telephone: 416-291-8085
Toll Free: 800-265-1775
Fax: 416-298-4328
Email: info@plexpack.com
www.plexpack.com



PLEXPACK

PLEXPACK Machinery Distributed By: