

# SHRINK TUNNEL

MODEL: T3422



## FEATURES

### TUNNEL CHAMBER

- Digital Tunnel Temperature Control
- High Velocity Air Flow with Dual Mechanical Controls
- Open Coil Heating Element Guaranteed for 10 Years
- Two Heat Zones
- High Temperature Limit Switch
- Automatic Cool Down Extends Heating Element Life

### CONVEYOR FEATURES

- Quick Change 1/2" Diameter Live/Dead Rollers with 2" Spacing
- Unique Pre-Shrink Feature Allows For 25% More Bottom Shrink
- One Quarter Horsepower Motor With Adjustable Conveyor Speeds Of Up To 70 Feet Per Minute



Model T3422

### OTHER FEATURES

- Heavy Gauge Adjustable Height Console With Levelers And 3" Casters
- Stainless Steel Model Available
- Two Year Warranty

## MODEL SPECS

<b>INSIDE TUNNEL DIMENSIONS</b>	34" L, 22" W, 10" H (86 cm L, 56 cm W, 25 cm H)
<b>CONVEYOR</b>	Variable Speed, Quick Change Live/Dead Silicone Covered Rollers with 2" Spacing
<b>CONVEYOR SPEED</b>	0 - 30 ft./min. (9 m./min.) 0 - 70 ft./min. LDR (0 - 21 m./min. LDR)
<b>OVERALL DIMENSIONS</b>	60" L, 31" W, 57" H (153 cm L, 79 cm W, 145 cm H)
<b>POWER REQUIREMENTS</b>	220 Volts, 54 Amps Single Phase
<b>WATTAGE</b>	10,000 Watts
<b>WEIGHT</b>	560 lbs. (255 kg)

## AVAILABLE OPTIONS

- Stainless Steel Construction (T3422S)
- Stainless Steel Wire Mesh Belt Conveyor
- Non-stick Mesh Belt Conveyor (TMB)
- Non-stick Mesh Belt Overlay (For Live / Dead Roller Conveyor)
- Roller Spacing: 1"
- Roller Spacing: 1 1/2"
- Pack Cooler Fan (For Polyethylene)
- Hydraulic Easy Lift Adjustable Height Console
- 14" High Tunnel Opening
- Left Hand Reverse Flow

