

## TECHNOPLAT 708 CW

SEMI-AUTOMATIC STRETCH WRAPPER

Increase productivity and keep your operators safe by keeping them on the fork truck.

- Heavy duty clamp, cut and welding unit
- Keep driver in the driver's seat where they can be the most productive.
- 110" Wrap Height Standard
- Remote Control included
- Cube Technology delivers the right amount of film at exactly the right position with exactly the right containment force
- Multi-Level Variable Containment Force is optimized at each level and is adjustable up to nine (9) times on each load.
- CUBE Technology will reduce your film usage by 30% – 55%.
- R-Connect now included as standard feature (includes 36-month initial cellular data plan).



## Performance features:



### CLAMP, CUTTING AND WELDING UNIT

Ensure a perfect adherence of the film to the load for better containment with the cut, clamp, and welding system (CW). The new aluminum clamp controlled by a pneumatic cylinder holds the film clearly and without slippage during cutting.

### COLOR TOUCH SCREEN

The high performance 7-inch color touch screen with icons specifically designed and created by Robopac has led to the implementation of the MULTILEVEL CONTROL function.



### PVS CARRIAGE

Powered stretch system controlled by two motors. Stretch ratio adjustable from panel board from 150-400%. Force to the load controlled by patented electronic device and adjustable from panel board.

**Rconnect standard**, a technologically advanced monitoring system combines innovation and connection, allowing complete control of the operation of the machines and a total support to the final customer. Monitor and improve your performance with remote assistance.



### Remote Control

The remote control comes standard with the Technoplat and can control up to 4 units.



## Technoplat 708 CW Specifications

### Performance Criteria

#### Production Speed:

Up to 40 LPH

#### Turntable Speed:

5 – 15 RPM

#### Turntable Drive:

1 HP VAC

### Load Handling System

#### Turntable Size:

65" Diameter

#### Maximum Load Dimensions:

40" W x 48" L x 110" H

#### Maximum Load Height:

110" Standard

#### Maximum Load Weight:

4400 lbs.

### Film Delivery System

- Multi-Level Variable 100 – 400%
- Containment Force: Variable Load Cell
- Film Carriage Motor: ½ HP VAC Chain Driven
- Height Sensing: Automatic via photocell
- Film threading: Patented S-Pattern
- Corner Compensation: Load Cell
- Standard Film Width – 20" (30" option)

### Safety Features

- Anti-Fall Device on Carriage
- Pressure activated safety stop on carriage
- CE Compliant, UL, CUL

### Hardware

#### Voltage:

110V, 20 AMP, 60 Hz, 1 PH

#### Air:

60 PSI

#### NEMA 12 Enclosure

Standard

#### Warranty:

5 Years