

# EMPLEX

## BAG SEALING SOLUTIONS

## MPS 7500

### Series Continuous Band Sealer

The MPS 7500 series are conveyORIZED bag sealers capable of sealing bags of any weight. These sealers can seal bags up to 12 mil / 300 micron in thickness at production rates (6 mil / 150 wide maximum when gusseted). These sealers are also ideal for when the speed of an MPS 6000 series machine is not enough to meet your manufacturing needs. The MPS 7500 comes standard with a S.S. 6" / 150 mm wide x 6' / 1.8 m long, adjustable height, food grade belt conveyor. The sealer and the conveyor each have their own 1/8 hp motors and the speed of the system is electronically synchronized. Designed for 24/7 operation, these sealers are suitable for all production environments.



<b>Electrical:</b>	120 volts, 11 amps.
<b>Infeed Direction:</b>	Right to Left.
<b>Motor:</b>	Variable Speed DC drive.
<b>Seal Throat Depth:</b>	70 mm / 2.75".
<b>Sealing Section:</b>	254 mm / 10" of heating. 254 mm / 10" of cooling.
<b>Variable Speed:</b>	Up to 20 m / 800" per minute.
<b>Sealing Width:</b>	6 mm / 1/4" standard.
<b>Sealer Operation:</b>	Vertical or Horizontal.
<b>Temperature Range:</b>	0-230 degrees C. 0-445 degrees F.
<b>Temperature Controller:</b>	Digital PID autotune

<b>Model</b>	<b>Configuration</b>
<b>MPS 7500</b>	Conveyorized Sealer
<b>MPS 7510</b>	Conveyorized Sealer with Front End Trimmer
<b>MPS 7520</b>	Conveyorized Sealer with Emboss Coder
<b>MPS 7530</b>	Conveyorized Sealer with Dry Ink Printer
<b>MPS 7550</b>	Conveyorized Sealer with Front End Trimmer & Dry Ink Printer
<b>MPS 7560</b>	Conveyorized Sealer with Front End Trimmer & Emboss Coder

Telephone: 416-291-8085  
 Toll Free: 800-265-1775  
 Fax: 416-298-4328  
 Email: info@plexpack.com  
 www.plexpack.com

**PLEXPACK**



PLEXPACK Machinery Distributed By: