



HANDLE-IT® RA Series

Model 2200AA-C

Model 2300AA-C



Part Number: SWM-RA-2200AA-C

Automatic film attach, cut, and hot weld sealing unit

250% Power Pre-Stretch Carriage

300 max average pallets per day!

Technical Specifications

Wrap Height	94"
Machine Dimensions	125" L x 112" w x 140" h
Max Pallet Size	40" x 48"
Weight Capacity	Unlimited
Pre-Stretch	250% Powered
Power Supply	110V, 10 Amp
Total Machine Footprint	93" long x 60" wide
Machine Weight	1100lbs
Arm Speed	12 RPM

Handle-It® Model 2200AA-C

The Handle-It® Model 2200AA-C offers top-of-the-line functions and features at a great price. It is ideal for those who are looking for an efficient machine capable of handling high volumes of pallets per day.

Standard features on the 2200AA-C include 250% powered pre-stretch, 94" max wrap height, user-friendly control panel, electronic film tension, automatic film attach, cut and hot weld film tail sealing, and many other elements cleverly designed to make this unit a must-have in any facility looking to improve and streamline their packaging operations.

HANDLE-IT®

Automatic Stretch Wrapper

Model 2200AA-C

Product Specifications

- Electronic printed circuit board for the management of the cycle
- Frequency controller for rotation speed adjustment (from 3 to 12 RpM)
- 250% Powered Pre-stretch Film Carriage
- Frequency controller for carriage speed adjustment (speed going up and speed going down can be set differently)
- Maximum wrapping height: 94"
- Maximum size of the pallet: 40" x 48"
- Maximum loading weight: Unlimited
- Electromagnetic brake for film stretching
- Photocell for pallet height detection
- Safety stop loop at the base of the carriage
- Stop at 0 position
- Power board IP54
- 3 access keys (including lock mode)
- Adjustable parameters by the control panel: cycle selection, bottom turns, top turns, rotation speed, carriage speed going up, carriage speed going down, film tension.
- 6 working cycles: ascent/descent; topsheet; only ascent; only descent; layers; stack
- 32 wrap programs can be saved by the customer
- 3 cycle types: semimanual, semiautomatic, and fixed height
- Acoustic warning at the cycle beginning and stop
- Wrapped Pallet counter
- Autodiagnostic
- Powder coating
- Braked arm at the end of the cycle



Options

- Adjustable power pre-stretch
- Photocell for Dark Loads
- Extended mast 118"
- Extended Arm for larger pallets
- Wall mounting hardware



Intuitive Control Board



Automatic Sealing Unit: Attaches, Cuts, & Hot welds the film tail