

WULFTEC® STRETCH WRAPPERS THE CAT - WCAT-450 Combo Arm Turntable



UP TO
45 RPM

**OVER 100
LOADS PER HOUR**

THE CAT The most versatile system in the industry

This versatile combo arm turntable wrapper allows the customer the possibility of switching operating modes: operation in only rotary arm mode 30 RPM, operation in only turntable mode 15 RPM or **operation in combo arm turntable mode 45 RPM.**

✓ **Productivity**

✓ **Versatility**

✓ **High Speed**

✓ **Film Saving**

CRAFTED FOR SUCCESS

This quality engineered automatic stretch wrapper features:

- Combined arm and turntable speed of 45 RPM
- Rotary arm AND turntable each driven by a 25" Heavy Duty Ring GEAR Bearing, with Pinion GEAR Drive
- Possibility to switch mode between arm wrapper, turntable wrapper or combo wrapper
- Dual chain carriage lift and dual structural steel boom
- 20" NO-THREAD® powered pre-stretch carriage
- Rotary arm and turntable separate speed controls
- Allen Bradley PLC with PanelView Plus 7 6" touch screen for easy to understand, easy to use interface
- NEMA 4/12 control cabinet with quick disconnect
- Intuitive diagnostic alarms and maintenance screens

✓ **Ideal for all industries**

✓ **Energy Saving Modes**

✓ **Possibility to index 90° in wrap zone**

✓ **Accurate positioning of arm and table to reduce film consumption**

✓ **Can be fed by more than one palletizer**



WWW.WULFTEC.COM
WE FEAR NO PACKAGING CHALLENGE

Technical Specifications

THE CAT (WCAT-450)

Production Rate ¹	Up to 120 loads per hour
Maximum Load Weight	5,000 lbs (6,000 lbs option)
Maximum Load Size	48" L x 48" W x 80" H
Machine Dimensions ²	265" L x 148" W x 140" H
Approx. Shipping Weight	12,000 lbs
Electrical Requirements	230V/3/60 (other voltage available)
Pneumatic Requirements	3 CFM @ 80 PSI; comes with Filter/Regulator
Controls	<ul style="list-style-type: none"> · NEMA 4/12 control cabinet with quick disconnect · Intuitive alarm diagnostics · On-screen wrapping performance analysis · AC drives and motors · On-screen maintenance program and instructions · Separate up and down carriage speeds · Allen Bradley PLC and Touch screen operator interface · Separate top and bottom wrap selection
Film Delivery System	<ul style="list-style-type: none"> · 20" NO-THREAD[®] powered pre-stretch carriage (angled carriage to wrap lower) · 50-300% pre-stretch · 1 HP AC motor with variable frequency drive and corner compensation
Film Tail Treatment	<ul style="list-style-type: none"> · Automatic film clamping (drop away design, no film tear) · Pulsed-controlled cutter · Film alignment arm and brush on film treatment
Rotary Arm Drive	<ul style="list-style-type: none"> · 30 RPM variable speed · 2 HP AC motor with variable frequency drive · 25" Heavy-duty Ring GEAR Bearing, with Pinion GEAR Drive
Turntable Drive	<ul style="list-style-type: none"> · 15 RPM variable speed · 1 HP AC motor with variable frequency drive · 25" Heavy-duty Ring GEAR Bearing, with Pinion GEAR Drive
Heavy-Duty Conveyors	<ul style="list-style-type: none"> · Two 8' in/out powered contoured conveyors with smooth transfer · Heavy-duty cast iron flange mounted bearings · 52" between frame rails · 3 load staging positions · 2½" dia. rollers on 3" centers
Structure	<ul style="list-style-type: none"> · Heavy-duty structural steel construction · Robust 4-legged design for more stability and less stress on the frame
Warranty	<ul style="list-style-type: none"> · 3-year unlimited cycle warranty · 10-year warranty on steel structure · 10-year warranty on 25" ring GEAR bearings · Lifetime warranty on pre-stretch rollers' blue compound



Contoured conveyors with smooth transfer



Combined arm and turntable speed of 45 RPM

Options Available

- 20" or 30" powered pre-stretch carriage
- Height extension
- Heat seal unit
- Top sheet dispenser
- Top platen
- 90° configuration
- and more...




Reduced energy usage by throughput anticipation: Conveyorized automatic machines will operate at a lower speed when the throughput from the line is slower and speed up to allow production bursts. For an average production line³, the energy savings would equal 20 x 40 watt lamps lit for 6 hours!

Reduced film waste by optimized resolution: We use a higher resolution positioning system to deliver the film in a more accurate quantity. This means an average film reduction of 4 feet of film per pallet when compared to other control systems! That's 60 miles³ of unstretched film per year!

Reduced general waste by better product protection for handling and transport: With very low wrap capability, the product is properly secured to the pallet, resulting in a pallet that is more stable for transport and therefore less damage!

Reduced electricity consumption: By using variable frequency drives on all its motors, Wulftec ensures that only the power required by the load is used, regardless of the HP of the motor. By this, we have standardized our motor sizes, allowing for less parts in inventory for us and our customers. This translates into greener operations at our end and at your end.



1. Production rate based on load and machine size and configuration
 2. Overall dimensions of machine in operation
 3. Based on a production rate of 60 pallets per hour, 2 shifts, where 50% of the production is in "peak-mode", 250% pre-stretch
- All machine specifications are subject to change without prior notice / Nominal dimensions shown



WULFTEC

A DURAVANT COMPANY

Wulftec International Inc.

209 Wulftec, Ayer's Cliff, Quebec, Canada JOB 1C0

Toll free: 877.WULFTEC (985.3832)

Phone: 819.838.4232

Fax: 819.838.5539

Email: wulftec@wulftec.com



WULFTEC IS A MEMBER OF THE DURAVANT FAMILY OF COMPANIES

FOOD SORTING & HANDLING | PROTEIN PROCESSING | PACKAGING | MATERIAL HANDLING

www.duravant.com