

SHRINK TUNNEL

MODEL: TX5218



FEATURES

TUNNEL CHAMBER

- Two Chamber Design with Dual Temperature Control
- Digital Temperature Adjustment with 9 Customized Program Settings
- Adjustable Air Flow
- High Temperature Safety Alarm
- Automatic Cool Down
- Schneider Electric Components

CONVEYOR FEATURES

- Digital Variable Speed
- Live/Dead Selection Roller Conveyor
- 3/8" (10mm) OD Roller on 1" (25mm) Pitch
- 20" (50cm) Roller Exit Conveyor



Model TX5218

OTHER FEATURES

- One Year Limited Warranty
- Powder Coated Steel Construction
- Heavy Duty Locking Casters

MODEL SPECS

INSIDE TUNNEL DIMENSIONS	52" L, 17.5" W, 8" H (134cm L, 45cm W, 21cm H)
CONVEYOR	Variable Speed, Quick Change, Live/Dead Rollers, 34" H (864mm)
POWER REQUIREMENTS	208-240 VAC, THREE PHASE 43A @208VAC, 49A @240VAC
WATTAGE	14 kW
OVERALL DIMENSIONS	64.5" L, 31.5" W, 57.5" H (163cm L, 80cm W, 146cm H)
WEIGHT	574 Lbs. (260 kg)

